



ALAS-125

Automotive Splice Tubing



Product Description

Grayline ALAS-125 is an adhesive lined heat shrinkable tubing designed specifically for automotive splice applications. When the tubing is heated, the outer wall shrinks while the inner wall melts and flows, encapsulating and sealing the components contained within. The 4:1 shrink ratio allows a limited range of sizes to cover a wide range of splice diameters. Grayline ALAS-125 is recommended for automotive applications requiring environmental sealing, fuel and fluid resistance, and electrical insulation.

*Standard Packaging: Reels or cut to customer specifications
Standard Color: Black, Clear**

Specifications

- EU Directive 2000/53/EC (ELV)
- EU Directive 2011/65/EU (RoHS2)

Features

- 4:1 Shrink Ratio
- Operating Temperature is -55°C to 125°C
- Shrinks at 125°C
- Creates an Environmental Seal
- Adheres to a Wide Variety of Substrates
- Flame Retardant (*Except in Clear)
- Lead-Free

Standard Sizes

NOMINAL SIZE	EXPANDED INSIDE DIAMETER (MINIMUM)	RECOVERED INSIDE DIAMETER (MAXIMUM)	RECOVERED WALL THICKNESS
1	.236	.055	.053
2	.315	.063	.069
3	.472	.098	.079
4	.708	.146	.102

The values listed in this bulletin, to the best of our knowledge, are accurate. They are typical performance results and are not intended to be used as design data. We disclaim all liability in connection with the use of information contained herein or otherwise.