



## GP80-AF-PVC

## General Purpose PVC Tubing



### Product Description

Grayline GP80-AF-PVC is an excellent general purpose flexible vinyl tubing. It features excellent elongation properties and good low temperature flexibility. This material contains an anti-fungal additive that makes it well suited for wet environments.

*Standard Packaging: Reels or Cut to Customer Specifications.*

*Standard Color: Black*

*Custom Sizes Available Upon Request*

### Specifications

- EU Directive 2000/53/EC (ELV)
- EU Directive 2011/65/EU (RoHS2)

### Features

- Operating Temperature is  $-35^{\circ}$  to  $60^{\circ}\text{C}$
- Low Temperature Flexibility
- Lead Free
- Fungus Resistant

PROPERTY	TYPICAL VALUE	TEST METHOD
Durometer Hardness, Shore A (15 Seconds)	80	ASTM D2240
Tensile Strength (psi)	2,200	ASTM D412
Elongation (%)	300	ASTM D412
Specific Gravity	1.41	ASTM D792
Brittleness Temperature, Pass $^{\circ}\text{C}$	-31	ASTM D746

*The values listed in this bulletin, to the best of our knowledge, are accurate. They are typical performance results and are not intended to be used as design data. We disclaim all liability in connection with the use of information contained herein or otherwise.*