



HWT

Heavy Wall Adhesive-Lined Polyolefin



Product Description

Grayline HWT is a heavy wall 3:1 adhesive lined heat shrinkable polyolefin. The inner adhesive wall melts and fills small voids to provide a complete environmental seal against water and dirt.

Standard Packaging: 4' Lengths (Cut-Lengths Available Upon Request)
Standard Colors: Black, Red

Specifications

- ANSI C119-1
- Western Underground Guide 2.4, 2.5
- EU Directive 2000/53/EC (ELV)
- EU Directive 2011/65/EU (RoHS2)

Features

- 3:1 Shrink Ratio
- Operating Temperature is -55°C to 110°C
- Shrinks at 120°C
- Flexible
- Creates an Environmental Seal
- Accepts Surface Markings
- Lead-Free

Standard Sizes

NOMINAL SIZE	EXPANDED INSIDE DIAMETER (MINIMUM)	RECOVERED INSIDE DIAMETER (MAXIMUM)	RECOVERED WALL THICKNESS
0350	0.350"	0.120"	.070"
0500	0.510"	0.160"	.080"
0750	0.750"	0.240"	.120"
1100	1.100"	0.350"	.120"
1500	1.500"	0.470"	.140"
2000	2.000"	0.630"	.140"
2700	2.700"	0.870"	.150"
3500	3.540"	1.180"	.150"
4700	4.720"	1.570"	.150"
5100	5.100"	1.570"	.150"
6000	6.000"	2.000"	.150"
6700	6.700"	2.230"	.150"

The values listed in this bulletin, to the best of our knowledge, are accurate. They are typical performance results and are not intended to be used as design data. We disclaim all liability in connection with the use of information contained herein or otherwise.