

NU-SLEEVE SG-200 HW




NU-SLEEVE SG-200 HW



Mechanical & Abrasion Protection
Thermal Protection



Uncoated & Coated Sleeving




Braided or knitted



Fiberglass
High temperature silicone rubber



Option: Black, red oxide
 Other colors upon request




Low: -60°C (-76°F)
High: 260°C (500°F)



Fireproof and waterproof protection
High thermal insulation
Heavy duty applications



 UZFT2 - VW1 Rating

NEMA TF1 - Type 5, SAE AS1072E
RoHS, REACH, CMRT

PHYSICAL PROPERTIES

Physical properties	Spec	Unit	Value
Operating temperature	-	°C (°F)	-70/260 (-94/500)
Short term temperature	-	°C (°F)	1200 (2200)
Thermal conductivity	ASTM D1518	W/mk	0.03
Dielectric strength	-	-	Grade A
Flammability	UL 1441 VW-1	-	pass
Chemical resistance	Resists to chemical and fluids		

DIMENSIONS

Designation	Indicative nominal Ø (mm)	
	inches	mm
NU-SLEEVE SG-200 HW 1/4	1/4"	6
NU-SLEEVE SG-200 HW 5/16	5/16"	8
NU-SLEEVE SG-200 HW 3/8	3/8"	10
NU-SLEEVE SG-200 HW 7/16	7/16"	11
NU-SLEEVE SG-200 HW 1/2	1/2"	13
NU-SLEEVE SG-200 HW 9/16	9/16"	14
NU-SLEEVE SG-200 HW 5/8	5/8"	16
NU-SLEEVE SG-200 HW 3/4	3/4"	19
NU-SLEEVE SG-200 HW 7/8	7/8"	22
NU-SLEEVE SG-200 HW 1	1"	25
NU-SLEEVE SG-200 HW 1 1/8	1 1/8"	29
NU-SLEEVE SG-200 HW 1 1/4	1 1/4"	32
NU-SLEEVE SG-200 HW 1 3/8	1 3/8"	34
NU-SLEEVE SG-200 HW 1 1/2	1 1/2"	38
NU-SLEEVE SG-200 HW 1 3/4	1 3/4"	45
NU-SLEEVE SG-200 HW 2	2"	51
NU-SLEEVE SG-200 HW 2 1/4	2 1/4"	57
NU-SLEEVE SG-200 HW 2 1/2	2 1/2"	64
NU-SLEEVE SG-200 HW 2 3/4	2 3/4"	69
NU-SLEEVE SG-200 HW 3	3"	76
NU-SLEEVE SG-200 HW 3 1/4	3 1/4"	82
NU-SLEEVE SG-200 HW 3 1/2	3 1/2"	88
NU-SLEEVE SG-200 HW 3 3/4	3 3/4"	95
NU-SLEEVE SG-200 HW 4	4"	101
NU-SLEEVE SG-200 HW 4 1/2	4 1/2"	114

PACKAGING

Coils, Cut lengths upon request

sales@delfingen.com • www.delfingen.com